



CP-Q3

CP-Q3 Series

80mm with Auto-cutter

260mm/second speed

3-in-1 interface Thermal Printer with Unrivalled Convenience



1. New to the scene

Incorporating the 3-in-1 interface (RS-232 + USB HID / USB Virtual COM + LAN) and 260mm/second high print speed onto the CP-Q3. The outstanding features help you easy print on your applications.

2. Wallet friendly

CP-Q3 is a revolutionary new design structure that features the very good reliability and stability on your printing . However , CP-Q3 printer is at the exceptional prices to meet your budget.

3. Powerful Drivers and OPOS support

- a. CP-Q3 supports Windows 9X/ME/2000/XP/NT/Vista Windows 7/8 and Linux operation systems.
- b. With OPOS drivers.

4. Data Buffer and NV Buffer

- a. 256 KB NV buffer to support the logo printing.
- b. 2048 KB Data buffer built-in.
- c. 4MB SPI Flash Memory

Ordering Information:

CP-Q3 : 80mm thermal receipt printer ,
w/Auto-Cutter , 260mm / second ,
RS-232 + USB HID /USB Virtual COM
+ LAN , Black color



Technical Specifications

Model Numbers	CP-Q3	Interface	Dsub 9 pin female connector, default with 9600 or up to 115200 bps baud-rate (straight)
Printer	Printing Method: Direct Thermal	Serial	
	Printing Direction: Line printing	USB	USB HID / USB Virtual COM
Mechanism	Max Print Width: 82.5mm ±0.5mm	Ethernet	10/100Base-T
	Effective Print Width: 72mm	Cash Drawer	DC 24V, 1A, RJ-11 socket
	Character Size: Font A: 12 x 24 dots ; Font B: 9 x 17 dots	Print commands	ESC/POS OPOS driver available
	Character per line: Font A: 48 ; Font B: 64	Input Buffer	256KB for NV Flash buffer 2048KB for Data receive buffer
	Printing Speed: 260mm/sec	SPI Flash Memory	4MB
Printer Head	Printer Density: 576 dots/line, 203dpi	Paper	Paper Width: 82.5mm ±0.5mm
	Life: 100 KM	Roll diameter	Max. 83mm
Print font	ASCII code: 13 international character set	Thickness	0.06~0.08mm
	Chinese: Big 5 / GB123	Environment	Operating: 0°C ~ 45°C; 10%RH ~ 80%RH
Bar code	1D: UPC-A/ UPC-E/ JAN13(EAN13)/ JAN8(EAN8)/ CODE39/ Interleaved 2 of 5/ CODABAR/ CODE93/ CODE128	Storage: -10°C ~ 60°C; 10%RH ~ 90%RH	Power supply Input: 100V AC – 220V AC, 50-60Hz (≤1.5A)
	2D: QR CODE / PDF417	Power supply Output: DC +24V / 2.5A	Dimension : 183(L) x 143.5(W) x 135mm (H)
Cutter	Auto Cutter: Full cut or Partial cut	Gross Weight : 3.5Kgs	Black Mark : Supported
	Life Span: 1,000,000 times	Sensor : Cover open sensor , Receipt coming alarm , Error alarm sensor	
Driver	Win9X/WinME/Win2000/WinNT/WinXP, Win Vista, Win7/WIN 8/Linux		



Birch is a trademark of Birch Technology U.S.A. Inc
All other products, brands or companies are trademarks or registered trademarks of their respective companies.

Specifications are subject to change without prior notice

Contact us for details